

PRODUCT DATA SHEET



TIPP-OIL Low Emission Diesel 10W-40

TIPP OIL Manufacturer GmbH Co. KG

Am Langen Kamp 2
59192 Bergkamen · Germany

Tel: (+49) 02307 9703274

Web: www.tippoil.com

Fax: (+49) 02307 9703275

E-Mail: contact@tippoil.com

Company registration number: HRA4299

VAT number: DE313987910

Revised on: 03.04.2025 | Number of the version: 01 | Replaces version: 01

Description of the

Tipp Oil Low Emission Diesel 10W-40 is a high-quality truck engine oil formulated with Low SAPS technology. It can be used in both older and new engines. Low Emission Diesel 10W-40 improves the performance, reliability and cleanliness of engines.

It reduces fuel consumption and wear as it reduces friction.

Application notes

TIPP-OIL Low Emission Diesel 10W-40 is ideally suited for Euro 5 engines with exhaust systems and in Euro 3 & 4 engines, if this is prescribed by the engine manufacturer.

Quality classification specifications:

- ACEA E6/E7/E9
- API CJ-4
- API SN/CF
- Global DHD-1
- JASO DH-2

Recommendation:

- Caterpillar ECF-2/ECF-3
- Cummins CES 20081
- DDC 93K218
- Deutz DQC III-10 LA
- Iveco 18-1804 TLS E9
- Mack EO-O Premium Plus
- MAN M 3575
- MB 228.51
- MTU Typ 2.1
- Renault VI RLD-3
- VOLVO VDS-4

Properties:

- Stable viscosity behaviour
- Protection against sludge, coking and varnish formation
- Excellent detergent and dispersant properties
- Very good wear and corrosion protection
- High oxidation stability and engine cleanliness

PRODUCT DATA SHEET



TIPP-OIL Low Emission Diesel 10W-40

TIPP OIL Manufacturer GmbH Co. KG

Am Langen Kamp 2
59192 Bergkamen · Germany

Tel: (+49) 02307 9703274

Web: www.tippoil.com

Fax: (+49) 02307 9703275

E-Mail: contact@tippoil.com

Company registration number: HRA4299

VAT number: DE313987910

Revised on: 03.04.2025 | Number of the version: 01 | Replaces version: 01

Technical characteristics:

Eigenschaften	Daten	Einheit	Prüfung nach:
kinematic viscosity at 40°C	92,7	MM²/S	DIN ISO 51562-2
kinematic viscosity at 100°C	14,2	MM²/S	DIN ISO 51562-2
viscosity index	158		DIN ISO 2909
appearance	Yellowbrown		
visuell density at 15°C	862	KG/M³	DIN EN ISO 12185
Pour Point	-39	CELSIUS	ASTM D 7346

All data given are approximate values and are subject to the usual production fluctuations. To the best of our knowledge, all information corresponds to the current state of knowledge and our development. We reserve the right to make changes. All references to DIN standards are for product description purposes only and do not constitute a guarantee. In the event of problems, please request technical advice.

26.07.2024 04:52:00