

PRODUCT DATA SHEET



TIPP OIL Mineral Super 10W

TIPP OIL Manufacturer GmbH Co. KG

Am Langen Kamp 2
59192 Bergkamen · Germany

Tel: (+49) 02307 9703274

Web: www.tippoil.com

Fax: (+49) 02307 9703275

E-Mail: contact@tippoil.com

Company registration number: HRA4299

VAT number: DE313987910

Revised on: 16.04.2025 | Number of the version: 01 | Replaces version: 01

Description of the

TIPP OIL Mineral Super 10W is a universally applicable high-performance monograde engine oil for use in lorry diesel engines with and without turbocharging as well as for stationary systems. Mineral Super 10W offers a balanced additive package and guarantees high wear and corrosion protection and corrosion protection.

Application notes

TIPP OIL Mineral Super 10W is used in lorry diesel engines with and without turbocharging as well as in stationary stationary systems. The operating instructions of the vehicle and engine manufacturers must be must be observed.

Quality classification specifications:

- API SF/CD
- CCMC G4
- MIL-L-2104 D
- MIL-L-46152 B

Recommendation:

- MB 227.0, MB 228.0, MB 235.27
- Voith Retarder A

Properties:

- High oxidation stability
- Good shear stability
- Prevention of wear
- Neutrality towards sealing materials
- Good cold start properties
- Very stable and excellent viscosity and temperature behaviour
- Good lubricating properties even at high oil temperatures
- Best suitability for difficult operating conditions
- Convincing detergent and dispersing properties
- Prevention of black sludge formation

PRODUCT DATA SHEET



TIPP OIL Mineral Super 10W

TIPP OIL Manufacturer GmbH Co. KG

Am Langen Kamp 2
59192 Bergkamen · Germany

Tel: (+49) 02307 9703274
Web: www.tippoil.com

Fax: (+49) 02307 9703275
E-Mail: contact@tippoil.com

Company registration number: HRA4299
VAT number: DE313987910

Revised on: 16.04.2025 | Number of the version: 01 | Replaces version: 01

Technical characteristics:

Eigenschaften	Daten	Einheit	Prüfung nach:
kinematic viscosity at 40°C	43,2	MM²/S	DIN ISO 51562-2
kinematic viscosity at 100°C	7,0	MM²/S	DIN ISO 51562-2
viscosity index	120		DIN ISO 2909
appearance	Yellowbrown		
visuell density at 15°C	863	KG/M³	DIN EN ISO 12185
Pour Point	-36	CELSIUS	ASTM D 7346

All data given are approximate values and are subject to the usual production fluctuations. To the best of our knowledge, all information corresponds to the current state of knowledge and our development. We reserve the right to make changes. All references to DIN standards are for product description purposes only and do not constitute a guarantee. In the event of problems, please request technical advice.
26.07.2024 04:52:00