

PRODUCT DATA SHEET



TIPP OIL Mineral Super 60 SAE 60

TIPP OIL Manufacturer GmbH Co. KG

Am Langen Kamp 2
59192 Bergkamen · Germany

Tel: (+49) 02307 9703274

Web: www.tippoil.com

Fax: (+49) 02307 9703275

E-Mail: contact@tippoil.com

Company registration number: HRA4299

VAT number: DE313987910

Revised on: 17.04.2025 | Number of the version: 01 | Replaces version: 01

Description of the

TIPP OIL Mineral Super 60 is a mineral monograde engine oil for petrol and diesel car engines petrol and diesel car engines with and without turbocharging and commercial vehicle engines. Mineral Super 60 is characterised by its good high-temperature properties, minimisation of fuel consumption, friction and wear, friction and wear. Mineral Super 60 is a reliable and highly resilient engine oil.

Application notes

TIPP OIL Mineral Super 60 is designed for use in petrol and diesel car engines as well as commercial vehicle engines. designed. Mineral Super 60 can be used in engines with the stated specifications.

The operating instructions of the automobile and engine manufacturers must be observed.

Quality classification specifications:

- API-SF/CF
- CCMC G4
- MIL-L-2104 D
- MIL-L-46152 B

Recommendation:

- MB 228.0/227.0

Properties:

- Stable and excellent viscosity behaviour
- Good cleaning and dispersing properties
- Suitability for catalysers
- Very good shear stability
- Prevention of black sludge formation
- High oxidation stability

PRODUCT DATA SHEET



TIPP OIL
Mineral Super 60
SAE 60

TIPP OIL Manufacturer GmbH Co. KG

Am Langen Kamp 2
59192 Bergkamen · Germany

Tel: (+49) 02307 9703274
Web: www.tippoil.com

Fax: (+49) 02307 9703275
E-Mail: contact@tippoil.com

Company registration number: HRA4299
VAT number: DE313987910

Revised on: 17.04.2025 | Number of the version: 01 | Replaces version: 01

Technical characteristics:

Eigenschaften	Daten	Einheit	Prüfung nach:
kinematic viscosity at 40°C	295,3	MM²/S	DIN ISO 51562-2
kinematic viscosity at 100°C	23,6	MM²/S	DIN ISO 51562-2
viscosity index	101,0		DIN ISO 2909
appearance	Yellowbrown		
visuell density at 15°C	896	KG/M³	DIN EN ISO 12185
Pour Point	-12	CELSIUS	ASTM D 7346

All data given are approximate values and are subject to the usual production fluctuations. To the best of our knowledge, all information corresponds to the current state of knowledge and our development. We reserve the right to make changes. All references to DIN standards are for product description purposes only and do not constitute a guarantee. In the event of problems, please request technical advice.
26.07.2024 04:52:00