

PRODUCT CERTIFICATE



TIPP OIL Manufacturer GmbH Co. KG

Am Langen Kamp 2
59192 Bergkamen · Germany

Tel: (+49) 02307 9703274
Web: www.tippoil.com

Fax: (+49) 02307 9703275
E-Mail: contact@tippoil.com

Company registration number: HRA4299
Sales tax identification number: DE331814405

Revised on: 10.07.25 | Number of the version: 02 | Replaces version: 01

TIPP-OIL Outboard 10W-40 COLORLESS

Description:

TIPP-OIL Outboard 10W-40 COLORLESS is a semi-synthetic outboard 4-stroke engine oil based on selected base oils and special additives which ensure perfect lubrication and a high level of wear protection. Outboard 10W-40 COLORLESS is particularly suitable for the lubrication of 4-stroke outboard engines with very high speeds and heavy loads. Outboard 10W-40 COLORLESS fulfils the requirements of the National Marine Manufacturers Association NMMA FC-W.

Instructions for use:

TIPP-OIL Outboard 10W-40 COLORLESS is suitable for all FC-W oil recommended outboard engines. The operating instructions of the engine manufacturer must be observed. Outboard 10W-40 COLORLESS is particularly recommended for outboard engines from Mercury Verado, Tohatsu/Nissan, Johnson/Evinrude, Yamaha, Honda and Suzuki. Outboard 10W-40 COLORLESS can also be used for engines in seawater operation.

Specification:

- API SM
- NMMA FC-W, NMMA FC-W (CAT)

Recommendation:

- Honda
- Johnson/Evinrude
- Mercury/Verado
- Suzuki
- Tohatsu/Nissan
- Yamaha

Features & Benefits:

- Perfect lubrication of all engine parts
- Very high wear, oxidation and corrosion protection
- Excellent shear stability
- Strong cleaning effect and residue-free combustion without deposits
- Adhesive, pressure and temperature-resistant oil film

PRODUCT CERTIFICATE



TIPP-OIL
Outboard 10W-40
COLORLESS

TIPP OIL Manufacturer GmbH Co. KG

Am Langen Kamp 2
59192 Bergkamen · Germany

Tel: (+49) 02307 9703274

Fax: (+49) 02307 9703275

Web: www.tippoil.com

E-Mail: contact@tippoil.com

Company registration number: HRA4299

Sales tax identification number: DE331814405

Revised on: 10.07.25 | Number of the version: 02 | Replaces version: 01

Technical specifications:

Properties	Data	Unit	Testing under
kinematic viscosity at 40°C	92,5	MM ² /S	DIN ISO 51562-2
kinematic viscosity at 100°C	14,2	MM ² /S	DIN ISO 51562-2
viscosity index	164		DIN ISO 2909
appearance	Yellowbrown		VISUELL
density at 15°C	858	KG/M ³	DIN EN ISO 12185
Pour Point	-36	°C	ASTM D 7346

All declared values are approximate and subject to standard production variations. To the best of our knowledge all information reflects the current state of findings and our development.

Subject to change. Any reference to DIN standards are solely for product description purposes and do not represent a guarantee. If problems arise, please consult a technician. 26.04.2022 02:00:00